

# DALI DT8 Constant Current Driver

## Product Feature

- . Comply to DALI Standard protocol IEC62386
- . DALI Digital control input, PWM output
- . Flicker-free ,BVM ≤ 0.4 ;ErP design: ≤ 0.5W
- . Short Circuit /Overload / temperature protection

## Advantages

- .Dimming range is 1%-100%
- .Dimming depth: 0.1%;
- .Built-in MCUS , Dimming process is smooth without dithering
- .Compatible with Dali and PUSH signal,2 in1 dimmable driver



### 8-10W DALI DT8 Mixed color Dimmable Driver

ERP CE CB SAA PFC ROHS

Model	Output Voltage DC	Output Current	Max power	Input Voltage AC	PFC	ERP	IP	Signal Standard	SIZE mm	N.W g
KMD-08-2DALI-E2	32-40V	200mA/2CH	8W	100-264V	0.95	0.5W	20	DT8	100x32x20	70g
KMD-10-2DALI-E2	32-40V	250mA/2CH	10W	100-264V	0.95	0.5W	20	DT8	100x32x20	70g



### 8-15W DALI DT8 Mixed color Dimmable Driver

ERP CE CB SAA PFC ROHS

Model	Output Voltage DC	Output Current	Max power	Input Voltage AC	PFC	ERP	IP	Signal Standard	SIZE mm	N.W g
KMD-08-2DALI-E3	32-40V	200mA/2CH	8W	100-264V	0.95	0.5W	20	DT8	100x32x20	70g
KMD-10-2DALI-E3	32-40V	250mA/2CH	10W	100-264V	0.95	0.5W	20	DT8	100x32x20	70g
KMD-12-2DALI-E3	32-40V	300mA/2CH	12W	100-264V	0.95	0.5W	20	DT8	100x32x20	70g
KMD-15-2DALI-E3	32-40V	350mA/2CH	15W	100-264V	0.95	0.5W	20	DT8	100x32x20	70g

# DALI DT8 Constant Current Driver

## Product Feature

- . Comply to DALI Standard protocol IEC62386
- . DALI Digital control input, PWM output
- . Flicker-free ,BVM ≤ 0.4 ;ErP design: ≤ 0.5W
- . Short Circuit /Overload / temperature protection

## Advantages

- .Dimming range is 1%-100%
- .Dimming depth: 0.1%;
- .Built-in MCUS , Dimming process is smooth without dithering
- .Compatible with Dali and PUSH signal,2 in1 dimmable driver



## 15-20W DALI DT8 Mixed color Dimmable Driver

ERP CE CB SAA PFC ROHS

Model	Output Voltage DC	Output Current	Max power	Input Voltage AC	PFC	ERP	IP	Signal Standard	SIZE mm	N.W g
KMD-15-2DALI-E1	25-40V	410mA/2CH	15W	220-240V	0.95	0.5W	20	DT8	96x43x30	80g
KMD-18-2DALI-E1	25-40V	500mA/2CH	18W	220-240V	0.95	0.5W	20	DT8	96x43x30	80g
KMD-20-2DALI-E1	25-40V	550mA/2CH	20W	220-240V	0.95	0.5W	20	DT8	96x43x30	80g